

Specifications

Models	GS-3390		GS-4390		GS-5390	
Measurements	Metric	US	Metric	US	Metric	US
Working height maximum*	11.94 m	39 ft 2 in	14.75 m	48 ft 4 in	17.95 m	58 ft 10 in
A Platform height maximum	9.94 m	32 ft 6 in	12.75 m	41 ft 9 in	15.95 m	52 ft 3 in
B Platform height - stowed**	1.55 m	5 ft 1 in	1.80 m	5 ft 11 in	2.02 m	6 ft 7.5 in
C Platform length outside:	3.98 m	13 ft 0.5 in	3.98 m	13 ft 0.5 in	3.98 m	13 ft 0.5 in
extended - single deck	5.34 m	17 ft 6.25 in	5.34 m	17 ft 6.25 in	5.34 m	17 ft 6.25 in
extended - dual deck	6.57 m	21 ft 6.5 in	6.57 m	21 ft 6.5 in	6.57 m	21 ft 6.5 in
D extended - super deck	7.38 m	24 ft 2.5 in	7.38 m	24 ft 2.5 in	7.38 m	24 ft 2.5 in
E Slide-out platform extension deck - front	1.52 m	5 ft	1.52 m	5 ft	1.52 m	5 ft
F Slide-out platform extension deck - rear	1.22 m	4 ft	1.22 m	4 ft	1.22 m	4 ft
G Platform width - outside	1.83 m	6 ft	1.83 m	6 ft	1.83 m	6 ft
H Height - stowed: folding guardrails rails lowered	2.71 m	8 ft 10.5 in	2.93 m	9 ft 7.5 in	3.15 m	10 ft 4 in
A Length - stowed: single deck	3.94 m	12 ft 11.25 in	3.94 m	12 ft 11.25 in	4.88 m	16 ft
dual deck	3.98 m	13 ft 0.5 in	3.98 m	13 ft 0.5 in	4.88 m	16 ft
super deck	4.81 m	15 ft 9.5 in	4.81 m	15 ft 9.5 in	4.88 m	16 ft
with outriggers	4.88 m	16 ft	4.88 m	16 ft	4.88 m	16 ft
Length - extended: single deck	5.40 m	17 ft 9 in	5.40 m	17 ft 9 in	5.40 m	17 ft 9 in
dual deck	6.57 m	21 ft 6.5 in	6.57 m	21 ft 6.5 in	6.57 m	21 ft 6.5 in
super deck	7.38 m	24 ft 2.5 in	7.38 m	24 ft 2.5 in	7.38 m	24 ft 2.5 in
A Width: standard tyres	2.29 m	7 ft 6 in	2.29 m	7 ft 6 in	2.29 m	7 ft 6 in
K Wheelbase	2.84 m	9 ft 4 in	2.84 m	9 ft 4 in	2.84 m	9 ft 4 in
A Ground clearance - center	0.36 m	1 ft 2 in	0.36 m	1 ft 2 in	0.36 m	1 ft 2 in

Productivity

Maximum platform occupancy	7	7	7	7	4	4
Lift capacity	1,134 kg	2,500 lbs	680 kg	1,500 lbs	680 kg	1,500 lbs
Drive height	full height		full height		9.14 m	30 ft
Lift capacity - extension deck	227 kg	500 lb	227 kg	500 lb	227 kg	500 lb
Drive speed - stowed	8.0 km/h	5.0 mph	8.0 km/h	5.0 mph	8.0 km/h	5.0 mph
Drive speed - raised	1.1 km/h	0.7 mph	1.1 km/h	0.7 mph	1.1 km/h	0.7 mph
Gradeability - stowed***	50%		50%		40%	
Maximum outrigger levelling****	7°(front to back)/12°(side to side)		7°(front to back)/12°(side to side)		7°(front to back)/12°(side to side)	
Turning radius - inside	2.16 m	7 ft 1 in	2.16 m	7 ft 1 in	2.16 m	7 ft 1 in
Turning radius - outside	5.33 m	17 ft 6 in	5.33 m	17 ft 6 in	5.33 m	17 ft 6 in
Raise / lower speed	45 / 29 sec		45 / 39 sec		55 / 49 sec	
Controls	proportional		proportional		proportional	
Drive	four wheel		four wheel		four wheel	
Tyres - foam-filled rough terrain	30 x 84 cm	12 x 33 in	30 x 84 cm	12 x 33 in	30 x 84 cm	12 x 33 in

Power

Power source	Deutz D2011L03i diesel 3 cylinder,49hp(37kW) Stage IIIA Deutz TD2.2 L3 turbo diesel 3 cylinder, 49hp(37kW) Stage V					
Auxiliary Power unit	12 V DC		12 V DC		12 V DC	
Fuel tank capacity	113.6 L	30 gal	113.6 L	30 gal	113.6 L	30 gal
Hydraulic system capacity	113.6 L	30 gal	113.6 L	30 gal	113.6 L	30 gal

Sound & Vibration Levels


Sound pressure level (ground workstation)	88 dBA	88 dBA	88 dBA	88 dBA	88 dBA	88 dBA
Sound pressure level (platform workstation)	78 dBA	78 dBA	78 dBA	78 dBA	78 dBA	78 dBA
Vibration	<2.5 m/s ²	8 ft 2 in/s ²	<2.5 m/s ²	8 ft 2 in/s ²	<2.5 m/s ²	8 ft 2 in/s ²

Weight*****

CE base machine	5,433 kg	11,977 lbs	5,849 kg	12,894 lbs	7,515 kg	16,567 lbs
The basic unit has the single extension deck, diesel motor, no outriggers (except standard on GS-5390), foam-filled or non-marking tyres, CE link guard and CE load sense.						
Unit weight modifiers for options						
Outriggers****	add 760 kg	1,675 lbs	add 779 kg	1,717 lbs	—	—
Dual Extension decks	add 356 kg	784 lbs	add 356 kg	784 lbs	add 356 kg	784 lbs
Super decks	add 411 kg	906 lbs	add 411 kg	906 lbs	add 411 kg	906 lbs
Generator	add 48 kg	105 lbs	add 48 kg	105 lbs	add 48 kg	105 lbs

Standards Compliance

EU Directives: 2006/42/EC - Machinery (harmonized standard EN280:2013+A1:2015);
2004/108/EC (EMC); 2000/14/EC (Outdoor Noise)



¹ GS-5390 comes standard with outriggers.
Machine length with outriggers represents overall length.
* The metric equivalent of working height adds 2 m to platform height.
** Based on RT tyres. Deduct 5.08 cm (2 in) for non-marking tyres.
*** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.
**** Outriggers are standard on GS-5390, optional on GS-3390 ad GS-4390
***** Weight will vary depending on options and/or country standards.

Features

Standard Features	Easily Configured To Meet Your Needs	Options & Accessories
-------------------	--------------------------------------	-----------------------

Measurements

GS-3390

- 11.94 m (39 ft 2 in) working height
- Up to 1,134 kg (2,500 lbs) lift capacity

GS-4390

- 14.75 m (48 ft 4 in) working height
- Up to 680 kg (1,500 lbs) lift capacity

GS-5390

- 17.95 m (58 ft 10 in) working height
- Up to 680 kg (1,500 lbs) lift capacity

Productivity

- Diamond plate deck
- Replaceable aluminum deck
- Folding guardrails
- Two self-closing full-height swing gates
- Proportional lift and drive
- Onboard diagnostic system
- Hydraulic oil cooler
- AC power to platform
- Positive traction control
- Four-wheel braking
- Tilt level sensor with audible alarm
- Descent alarm
- Dual Flashing LED beacons
- Horn
- Hour meter
- Telematics-Ready Connector

Power

- All engines are emissions compliant
- 12V DC auxiliary power
- Slide-out engine tray

Platform Options

- 3.98 x 1.83 m (13 ft 0.5 in x 6 ft) steel frame platform (standard)
- 1.52 m (5 ft) slide-out extension deck (standard)
- Dual slide-out platform extension deck package⁽¹⁾, 1.52 m (5 ft) front and 1.22 m (4 ft) rear (optional)
- 7.38 m (24 ft 2.5 in) super deck platform extension package^(1,2) (optional)

Outrigger Options

- Automatic levelling hydraulic outriggers⁽¹⁾ (standard on GS™-5390, optional on GS™-3390 and GS™-4390)
- No outriggers

Engine

- Deutz D2011L03i diesel 3 cylinder, 49hp(37kW) Stage IIIA
- Deutz TD2.2 L3 turbo diesel 3 cylinder, 49hp(37kW) Stage V

Drive

- 4 x 4

Axle Options

- Oscillating axle (standard on GS™-3390, optional on GS™-4390 and GS™-5390)
- Non oscillating

Tyre Options

- Foam-filled rough terrain (standard)
- Foam-filled, non-marking rough terrain

Productivity Options

- Air line to platform
- Power to platform: plug, socket, with optional Residual-current Circuit Breaker with Overcurrent protection
- Biodegradable hydraulic oil
- Track & Trace ⁽³⁾ (GPS unit providing machine location & operating information)
- Motion alarm

Power Options

- Diesel catalytic scrubber muffler
- Low temperature cut-out module
- Engine heater
- 220V/50Hz or 110V/50Hz Generator for Big Deck scissors



⁽¹⁾ Factory fit option only

⁽²⁾ Requires automatic levelling outriggers

⁽³⁾ Includes a first 2 years subscription

United Kingdom and MESART

The Maltings, Wharf Road, Grantham NG31 6BH, T: +44 800 988 3739 (toll free), Fax +44 (0)1476 584334.

Middle East, Southern Africa, Russia and Turkey, T: +971 4 399 0381.

Visit www.genielift.com/en-gb/about-genie/locations to view our global locations list.

Worldwide Manufacturing And Distribution

Australia · Brazil · Caribbean · Central America · China · France · Germany · Italy · Japan · Korea · Mexico · Russia · Southeast Asia · Spain · Sweden · United Arab Emirates · United Kingdom · United States

Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2020 Terex Corporation.

